

Excellent chemical, abrasion and flame resistance

- Non-encapsulating design, suitable for work in confined spaces
- Provides an outstanding barrier against a wide range of chemicals
- Patented fabric system with chloroprene rubber on an aramid base fabric, providing excellent flame and abrasion resistance
- Certified to the toughest standard in Europe - EN 943-2



Anatomically designed face seal for optimum safety and comfort



Strong and flexible suit material with excellent abrasion and flame resistance, provided by the aramid base fabric and the outer layer of chloroprene rubber



Bayonet glove ring system for quick and simple glove exchange



Attached boots or sewn-in socks in the suit material



Gas-tight Protection




Re-usable



Applications

- Chemical Handling
- Emergency Teams
- Fire & Rescue Service
- First Response
- Hazmat Teams
- Industrial and Tank Cleaning
- Law Enforcement
- Petrochemicals

Material Construction



PRODUCT INFORMATION

	AlphaTec® FLASH TYPE T
Design	Non-encapsulating design type T (with face seal and without hump, BA worn outside the suit).
Garment material	Outer: Strong, flexible and flame retardant aramid fabric coated with chloroprene rubber. Inner: Chloroprene rubber and a multilayer barrier laminate.
Seams	Stitched with aramid thread for superior strength and durability. Covered on the outside with a chloroprene rubber tape and on the inside with a welded-on barrier laminate tape.
Face Seal	Anatomically designed rubber face seal.
Gloves & Attachments	2-part system with Ansell Barrier® #02-100 inner glove and AlphaTec® #38-628 Viton®/Butyl rubber glove. The gloves are attached with a Bayonet glove ring system, which offers quick and simple glove exchange.
Footwear & Attachments	Sewn-in socks/booties made of the suit material. Alternatively attached black nitrile rubber safety boots with European approval as Firemen's boots. The boots are fixed with an ergonomically designed ring attachment, for simplified boot exchange.
Zipper	AlphaTec® HCR zipper, which includes a barrier film for increased chemical resistance. The zipper is closing downwards, for added safety, and is protected by a flap/splash guard.
Ventilation	A ventilation system is included as standard. For the safety of the wearer, it provides a constant level of overpressure inside the suit. The AlphaTec® Regulating valve MkII has 3 ventilation rates (2, 30 and 100 l/min) plus zero/off position. CEJN 221 male coupling for connection to the SCBA (requires separate connection hose). One overpressure valve on the chest.
Colour	Orange or olive green.
Sizes	XXS - XXXL
Included with each delivery	<ul style="list-style-type: none"> • 1 pce AlphaTec® Mini Hood for protection against inward leakage between mask and face seal, in case of jet spray from behind • 1 pair of cotton comfort inner gloves • 2 pcs extra locking pins for the Bayonet glove ring system • 1 pce Molycote lubrication for the O-rings in the Bayonet glove ring system • 1 pce grease stick for lubrication of the zipper • 1 pair of comfort silicone oversocks (only for suits with sewn-in socks) • 1 pce coat hanger • 1 pce AlphaTec® storage bag
Optional accessories	<ul style="list-style-type: none"> • Waist belt, internal • D-ring for holding small measuring instruments & tools • Customised marking, e.g. digits, letters, logos • AlphaTec® #58-800 Overglove for improved cut & puncture resistance • AlphaTec® SCBA Cover • Other accessories are available upon request
Standards & Approvals	<ul style="list-style-type: none"> • EN 943-1:2015 and EN 943-1/FprA1:2018 • EN 943-2:2002 and FprEN 943-2:2018 • EN 1073-2:2002 (radioactive particle protection) • EN 14126:2003 (infective agent protection) • EN 1149-5:2008 (antistatic suit material) • Approved for use in ATEX zones 2/21, 22 and chemical group IIA

For additional information, visit us at protective.ansell.com or contact us at:

Ansell Protective Solutions AB
Arenagatan 8B
215 33 Malmö
Sweden
Tel. + 46 10 205 1800
order.protective@ansell.com

Europe, Middle East and Africa
Ansell Healthcare Europe NV
Riverside Business Park
Blvd International, 55
1070 Brussels, Belgium
Tel. + 32 2 528 74 00
Fax + 32 2 528 74 01
info.europe@ansell.com

Latin America & Caribbean
Ansell Brazil Ltda.
Rua das Figueiras 474 – 4º Andar
Bairro Jardim
SP 09080-300 Santo André, Brazil
CNPJ: 03.496.778/0001-21
+55 11 3356 3100
sac@ansell.com

North America
Ansell Healthcare LLC
111 Wood Avenue South, Suite 210
Iselin, NJ 08830, USA
Tel. + 1 800 800 0444
Fax. + 1 800 800 0445
info@ansell.com

Asia Pacific
Ansell Protective Solutions Singapore Pte. Ltd.
237, Pandan Loop,
#05-05 Westech Building
128424 Singapore
Tel. + 65 6908 4115
order.protective@ansell.com

Performance Standards



TYPE 1a-ET



EN 1073-2



EN 14126



EN 1149-5

EN 1149-5:
This applies
only to the
suit material.