

FLAMMABLE LIQUID STORAGE CABINET - 250L

PRODUCT CODE: **DIL5545AS**



DESCRIPTION

Double door flammable liquids storage cabinets with 250L capacity.

Suitable for the storage of Class 3 flammable and combustible liquids including paint, solvents, petrol, thinners, kerosene, turpentine, white spirits, alcohol, ethanol, diesel, linseed oil and more.

Manufactured to meet the AS 1940 standard for the safe storage and handling of flammable and combustible liquids.

EXTERNAL DIMENSIONS (MM)

HEIGHT	WIDTH	DEPTH
1825	1115	500

INTERNAL DIMENSIONS (MM)

HEIGHT	WIDTH	DEPTH
1545	1020	415

NOTE:

For single door cabinets, the internal height is taken from the top of the sump sill/bottom shelf to the ceiling.

For total external width measurement, add 6mm vent bung for tight clearance locations.

KEY FEATURES

- Double steel walls
- Sequential opening doors ensure left door always closes first
- Solvent-resistant powder coating
- 150mm deep liquid light sump
- Recessed door handle with key lock
- 50mm vent bungs with flash arresters
- Static earthing connection
- Adjustable shelves
- Adjustable feet
- Classification labels

SPECIFICATIONS

CAPACITY: 250L

DOORS: 2

SHELVES: 3 (Including base level)

EXTRA SHELVES: **DIL5545-29**

